



## TECHNICAL DATA SHEET

### Zinc spray

**Artikelnr.**  
1521

**Bezeichnung D**  
Zinkspray, grau matt

**Bezeichnung FR**  
Spray de zinc, gris mat

**Bezeichnung EN**  
Zinc spray, grey matte

#### APPLICATION:




- Long-term corrosion protection agent
- For iron without topcoat, e.g. downpipes, ventilation units, steel structures and weld seams
- For indoor and outdoor use

#### ADVANTAGES:



- Long-term corrosion protection thanks to over 98% zinc dust content in the dry film
- Cathodic protection against corrosion and rust creep in wet or humid environments
- For iron and steel substrates
- Heat resistant up to 600 °C
- Fast drying
- High coverage
- Non-yellowing

#### SUBSTRATE:



- Suitable for iron, steel, aluminium and galvanized surfaces

Always test compatibility and adhesion on a small, inconspicuous area first.



## INSTRUCTIONS FOR USE:

### Preparation:



- The surface must be sanded, completely clean, dry, free from rust, dust and grease.
- Remove any flaking or brittle old coatings if necessary.

### Spray Application:



- Shake can thoroughly for 2 minutes.
- Test spray (e.g. on cardboard).
- Apply 2–3 thin coats in cross-coat technique at 25 cm spray distance.
- Allow flash-off between coats.
- Multiple layers increase corrosion protection.

### Drying Times:



- Dust-dry: after approx. 10 min
- Touch-dry: after approx. 20 min
- Fully cured: after approx. 24 hours

### Further Processing:




- Can be overcoated after approx. 15 min drying time.
- Can be recoated with itself at any time.

### End of Work:



- After finishing, turn can upside down and spray valve empty to prevent clogging.

### Coverage:



- 400 ml covers approx. 2 m².
- Depending on substrate and film thickness.

## TECHNICAL DATA:

Labeling: see safety data sheet

This information is given to the best of our knowledge and reflects our current state of knowledge. It is intended to inform about our products and their possible applications. It does not guarantee specific product properties or suitability for a particular purpose. As application and processing are beyond our control, they fall solely within the responsibility of the user. Preliminary testing is required.

Observe the warning notices on the product labels. Any existing property rights must be observed.