



TECHNICAL DATA SHEET Sealing Primer

Artikelnr.		Bezeichnung D
1071		Isoliergrundierung, weiss
6779		Premium Isoliergrundierung, weiss
		Bezeichnung FR
		Apprêt isolant, blanc
		Premium apprêt isolant, blanc
		Bezeichnung EN
		Sealing Primer, white
		Premium Sealing Primer, white

APPLICATION:



- Special primer for blocking water stains, nicotine, tar, bitumen, smoke stains, asphalt, etc.
- For interior and exterior use.
- Suitable for walls and ceilings.

ADVANTAGES:



Seals effectively



Dust dry in 15 minutes



Excellente adhesion



High coverage

- Effectively seals stains and prevents bleed-through to the topcoat.
- High insulating power
- Excellent adhesion
- Easy to apply
- Fast drying
- High yield
- Excellent overcoating with other dispersions and lacquers
- Professional application thanks to adjustable spray nozzle

SUBSTRATE:



- Plaster, hardboard, wood, stone, concrete, etc.
- Test compatibility and adhesion on an inconspicuous area first.



INSTRUCTIONS FOR USE:

Preparation:



- Substrate must be firm, clean, dry, and free from grease and release agents.

Spray Application:



- Shake can vigorously for 2 minutes. Test spray (e.g. on cardboard).
- Apply several thin cross-coats from a distance of 25 cm.
- Allow ventilation between spray passes.

Drying Times:



- Dust-dry: after approx. 15 minutes
- Touch-dry: after approx. 60 minutes
- Recoatable: after approx. 3 hours

Further Processing:




- Can be overcoated after approx. 3 hours drying time.
- Can be recoated with itself at any time.

End of Work:



- After use, turn can upside down and spray valve empty to prevent paint from drying in the nozzle.

Coverage:



- 400 ml covers approx. 2.2 m².
- Depending on substrate and layer thickness.

TECHNICAL DATA:

Labeling: see safety data sheet

This information is given to the best of our knowledge and reflects our current state of knowledge. It is intended to inform about our products and their possible applications. It does not guarantee specific product properties or suitability for a particular purpose. As application and processing are beyond our control, they fall solely within the responsibility of the user. Preliminary testing is required.

Observe the warning notices on the product labels. Any existing property rights must be observed.