

Brantho-Korrux®

Version: 06/25



TECHNICAL DATA SHEET Brantho-Korrux ALL-IN-ONE

Artikelnr.
verschiedene

Bezeichnung D
Brantho-Korrux, ALL-IN-ONE
Grundierung – Rostschutz – Lack

plusieurs

Désignation FR
Brantho-Korrux, ALL-IN-ONE
Primaire – Antirouille - Peinture

various

Designation EN
Brantho-Korrux, ALL-IN-ONE
Primer – Rust protection - Paint

APPLICATION:



- High-quality all-in-one spray paint with integrated rust protection
- combines primer, rust protection and top coat in one product
- Ideal for use on motorhomes, car parts, metal structures, classic cars and much more
- indoor and outdoor

ADVANTAGES:



Dust dry in
20 minutes



Applicable directly
onto rust




Excellente adhesion



High elasticity

- Can be applied directly onto rust – no sanding required
- High coverage, silky-gloss finish
- Resistant to weather, UV radiation & mechanical stress
- High elasticity & excellent edge coverage
- Dries quickly and evenly
- Outstanding adhesion on a wide variety of substrates

SUBSTRATES:



- **Metals:** iron, steel, stainless steel, aluminium, copper, zinc
- **Coatings & rust:** existing coatings, flash rust
- **Plastics:** hard plastics, GRP
- **Mineral substrates:** glass, concrete, screed

Test for compatibility and adhesion on a small, inconspicuous area beforehand.

RODARO GmbH
Erlistrasse 3
CH-6403 Küssnacht

T +41 41 390 14 53
E info@rodaro.ch
www.rodaro.ch

RODARO Germany GmbH
Marie-Curie-Strasse 2
D-79618 Rheinfelden
Sitz: Talstrasse 17, D-74223 Flein

T +49 7626 7479025
E info@rodaro.com
www.rodaro.com

Brantho-Korrux®

INSTRUCTIONS FOR USE:

Surface preparation:



- The substrate must be solid, clean, dry, free from grease and separating agents.
- Remove flash rust.

Spray application:



- Shake can vigorously for 2 minutes. Test spray (e.g. on cardboard)
- Apply several thin cross-coats from a distance of 25 cm
- Allow 2–3 minutes ventilation time between coats

Drying times:



- Dust-dry: after approx. 20–30 minutes
- Tack-free: after approx. 100 minutes
- Fully cured: after approx. 8–10 hours

Further processing:




- Recoatable after approx. 20–30 minutes
- Can be recoated with itself at any time.

After use:



- After finishing the application, turn the can upside down and spray until the nozzle is clear to prevent paint from drying inside.

Coverage:



- 400 ml covers approx. 3.0 m²
- Depending on substrate, color shade, and layer thickness

TECHNICAL DATA:

Labeling: see safety data sheet

This information is provided to the best of our knowledge and reflects the current state of our understanding. It is intended to inform about our products and their possible applications. It does not constitute a guarantee of specific properties or suitability for a particular purpose. Since application and processing are beyond our control, they are solely the responsibility of the user. Preliminary tests must be carried out.

Observe the safety instructions on the product labels. Any existing property rights must be taken into account.