



TECHNICAL DATA SHEET Universal Primer

Artikelnr.

1088
1095
1043

Bezeichnung D

Universal Primer, weiss
Universal Primer, grau
Universal Primer, schwarz

Bezeichnung FR

Primer universel, blanc
Primer universel, gris
Primer universel, noir

Bezeichnung EN

Universal Primer white
Universal Primer grey
Universal Primer, black

APPLICATION:



- Universal primer for interior and exterior use.
- Can be used as adhesion primer, filler, and anti-corrosion primer.

ADVANTAGES:



Dust dry in
10 minutes



Excellente
adhesion




High
coverage



Adjustable
spray nozzle

- Excellent adhesion
- Corrosion protection and filler in one
- Suitable for indoor and outdoor use
- Good flow and fast drying
- Can be applied wet-on-wet
- Weldable
- Overcoatable with all common 1K and 2K solvent-based and water-based topcoats
- Professional application thanks to adjustable spray nozzle

SUBSTRATES:



- Iron, steel, galvanized steel, aluminum
- GRP (glass-fiber reinforced plastic)
- Fully cured old paint
- Polyester substrates
- For plastics or old coatings:

Test for compatibility and adhesion on a small, inconspicuous area beforehand.

INSTRUCTIONS FOR USE:

Surface preparation:



- The surface must be sanded, completely clean, dry, and free from rust, dust, and grease.
- Remove flaking or brittle old coatings if necessary.

Spray application:



- Shake the can vigorously for 2 minutes. Perform a test spray (e.g., on cardboard).
- Apply 2 to 3 coats in a crisscross pattern from a distance of approx. 25 cm.
- Allow flash-off time between coats.

Drying times:



- Dust dry: after approx. 10 min
- Tack-free: after approx. 15 min
- Recoatable: after approx. 15 min
- Sandable: after approx. 20 min

Further processing:




- Can be recoated with itself at any time.
- Wet or dry sanding possible after approx. 20 min.
- Wet-on-wet application possible after approx. 15 min.

After use:



- After finishing the application, turn the can upside down and spray until the nozzle is clear to prevent paint from drying inside.

Coverage:



- 400 ml covers approx. 2.0 m²
- Depending on substrate, color shade, and layer thickness

TECHNICAL DATA:

Labeling: see safety data sheet

This information is provided to the best of our knowledge and reflects the current state of our understanding. It is intended to inform about our products and their possible applications. It does not constitute a guarantee of specific properties or suitability for a particular purpose. Since application and processing are beyond our control, they are solely the responsibility of the user. Preliminary tests must be carried out.

Observe the safety instructions on the product labels. Any existing property rights must be taken into account.