



TECHNICAL DATA SHEET HAMMERED SPRAY

Artikelnr.

2351

2368

Bezeichnung D

Hammerschlag Effekt, silber

Hammerschlag Effekt, schwarz-anthrazit

Bezeichnung FR

Peinture martelée effet, argent

Peinture martelée effet, noir-anthracite

Bezeichnung EN

Hammered spray, silver

Hammered spray, charcoal black

APPLICATION:



- For decorative coatings with a hammered finish
- Suitable for a wide range of materials
- For indoor and outdoor use

ADVANTAGES:



Dust dry
in 20 Min.



Hammered
effects



Very economical



Weather-
resistant

- Nostalgic hammered effects
- "Hammered" surface texture
- High opacity and fast drying
- Excellent flow and easy application
- Very economical in use
- Weather-resistant
- Ideal for mailboxes, stair railings, toolboxes, etc.

SUBSTRATE:



- Metal, wood, plastics, stone, clay, ceramics, glass as well as rattan/wicker and cardboard/paper, etc.
- Do not spray onto synthetic resin-coated surfaces – the paint may cause lifting
- Check plastic substrates for compatibility

Test first on a hidden area for compatibility and adhesion.



INSTRUCTIONS FOR USE:

Preparation:



- Thoroughly clean and sand the surface.

Spray Application:



- Shake can well for 2 minutes. Test spray (e.g. on cardboard).
- Spray at a distance of 25 cm using a cross-coat technique.
- Apply hammered-finish paint in the desired color as a light mist coat, then follow with a full coat.

Drying Times:



- Dust-dry: after approx. 20 min.
- Touch-dry: after approx. 60 min.
- Fully cured: after approx. 12 hours.

Further Processing:




- Can be overcoated with itself at any time.

End of Work:



- After finishing, turn can upside down and spray until valve is empty to prevent clogging.

Coverage:



- 400 ml covers approx. 2 m².
- Coverage depends on substrate and film thickness.

TECHNICAL DATA:

Labeling: see safety data sheet

This information is given to the best of our knowledge and reflects our current state of knowledge. It is intended to inform about our products and their possible applications. It does not guarantee specific product properties or suitability for a particular purpose. As application and processing are beyond our control, they fall solely within the responsibility of the user. Preliminary testing is required.

Observe the warning notices on the product labels. Any existing property rights must be observed.